



BLD102

LARGE ROUND BUILDER'S SERIES

DETAILS

Hammered Copper, Hammered Brass, Hammered Stainless Steel

Installation Type: Drop-In or Undermount

Brass: UB

Uses Standard 1.5" Drain

No Overflow

AVAILABLE FINISHES

AB	Antique Bronze
DB	Dark Bronze
SS	Satin Stainless Steel
PB	Polished Unlacquered Brass
PS	Polished Stainless Steel
UB	Satin Unlacquered Brass

AVAILABLE DRAINS

D004	Grid Strainer
D005	Lift and Turn
D006	Pop-up w/ lift rod
D101-D720	Decorative Drains

INSTALLATION

Drain should be installed first.

DROP-IN: Cut opening large enough for the sink to be "dropped in" to countertop.

UNDERMOUNT: Cuts in countertop are up to the discretion of the installer. Clips or other installation method must be provided by the fabricator/installer.


Use 100% silicone to adhere sink to countertop. Clean any excess silicone from sink surface.

CARE

Clean with mild soap. No abrasive chemicals

WARRANTY

Linkasink warranties our product to be free from manufacturing defect for the life of the product. Warranty does not cover abuse.



DIMENSIONS WILL VARY

DO NOT use this sheet as a guide for countertop cuts. Due to the handmade nature of each product, templates are not provided.