



C016A

SMALL FLAT ROUND

DETAILS

Installation Type: Drop-In or Undermount

Hand-Hammered Metal

No Overflow

Uses Standard 1.5" Drain

Each sink is hand-crafted; no two sinks will be the same

AVAILABLE DRAINS

| | |
|-------------|--------------------------------------|
| D004 | 1.5" Grid Strainer |
| D005 | 1.5" Lift & Turn |
| D006 | 1.5" Pop-up with Horizontal Pull Rod |
| D011 – D017 | Decorative Grid Strainers |
| D101 – D720 | Decorative Drains |

INSTALLATION

DROP-IN: Cut opening large enough for the sink to be "dropped in" to countertop.

UNDERMOUNT: Cuts in countertop are up to the discretion of the installer. Clips or other installation method must be provided by the fabricator/installer.

Use silicone to adhere sink to countertop. Clean any excess silicone from sink surface to avoid damaging the finish.

CARE

This sink has a living finish (excluding SS/PS) which will change with time and use. Nickel finishes are plated. Use mild soap and water for everyday cleaning. Avoid any harsh abrasives, acidic cleaning products and antibacterial hand soap. A paste wax may be applied periodically to protect the finish and help with water spotting.

WARRANTY

Linkasink warranties our product to be free from manufacturing defect for the life of the product. Warranty does not cover improper care, neglect, abuse, or normal wear-and-tear.

DIMENSIONS WILL VARY

DO NOT use this sheet as a guide for countertop cuts. Due to the handmade nature of each product, templates are not provided.

Contact: 602.971.2502

sales@linkasink.com

Linkasink may make changes to specifications without notice.

Visit linkasink.com for updated specification sheet.

8/10/2022